



YANG DONG

Technical Specifications



ENGINE

- YANG DONG series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled /turbocharged & air to water charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1, EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Over current load
- Low oil pressure
- High & low genset voltage
- High & low engine speed
- Start/stop failure
- Low radiator water level



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender





YANG DONG Series Diesel Generator Sets 12 - 15 - 22 - 28 - 34 kVA

MODEL			AYDJ 012	AYDJ 015	AYDJ 022	AYDJ 028	AYDJ 034	
GROUP	GEN-SET POWER	STAND BY	kVA	12	15	22	28	34
			kW	9,6	12	17,6	22,4	27,2
		PRIME	kVA	11	13,6	20	25,5	30,9
			kW	8,7	10,9	16	20,4	24,7
	CANOPY DIMENSION (W x L x H) mm			800x2000x1250	800x2000x1250	800x2000x1250	900x2200x1250	900x2200x1250
	CANOPY WEIGHT kg			649	670	717,6	756,6	946,6
	OPEN DIMENSION (W x L x H) mm			800x2000x1150	800x2000x1150	800x2000x1150	900x2200x1150	900x2200x1150
OPEN WEIGHT			502	524	563,6	602,6	771,6	
ENGINE	BRAND		YANG DONG	YANG DONG	YANG DONG	YANG DONG	YANG DONG	
	TYPE		YD385D	YD480D	YND485D	YSD490D	Y495D	
	POWER	STAND BY	kW	12	15,4	18,7	23,1	29,7
		PRIME	kW	11	14	17	21	27
	SPEED (rpm)		1500	1500	1500	1500	1500	
	CYCLE		4	4	4	4	4	
	DISPLACEMENT (lt)		1,532	1,809	2,156	2,54	2,977	
	NUMBER OF CYLINDERS		3 IN LINE	4 IN LINE	4 IN LINE	4 IN LINE	4 IN LINE	
	BORE x STROKE (mm x mm)		85 x 90	80 x 90	85 x 95	90 x 100	95 x 105	
	COMPRESSION RATIO		18 : 1	18 : 1	18 : 1	18 : 1	18 : 1	
	GOVERNOR TYPE		MECHANIC	MECHANIC	MECHANIC	MECHANIC	MECHANIC	
	INDUCTION		NATURAL	NATURAL	NATURAL	NATURAL	NATURAL	
	COMBUSTION SYSTEM		DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	
	COOLING SYSTEM		WATER	WATER	WATER	WATER	WATER	
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		3,55	4,22	4,71	5,45	6,87
		%75 PRIME POWER		3,12	3,43	3,73	4,05	6,15
%50 PRIME POWER		2,54	2,74	2,78	2,98	5,27		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)		4,5	5	5,5	8	8		
TOTAL COOLANT CAPACITY (lt)		11,1	11,3	12,5	14	14		
FUEL TANK CAPACITY (lt)		82	82	82	101	101		

Armak reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

Armak Makine Mühendislik İnş. San. ve Tic. Ltd. Şti.

Denizköşkler Mah. Tunay Sk. No:28
Avcılar / İSTANBUL / TURKEY

T: 0212 694 66 66

F: 0212 593 09 60

armakmakine@armakmakine.com

www.armakmakine.com