



Wilkins

Technical Specifications



ENGINE

- WILKINS series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled /turbocharged & air to water charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1,

EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Over current load
- Low oil pressure
- High & low genset voltage
- High & low engine speed
- Start/stop failure
- Low radiator water level



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender





WILKINS Series Diesel Generator Sets 250 - 275 - 300 - 330 kVA

MODEL				AWJ 250	AWJ 275	AWJ 300	AWJ 330
GROUP	GEN-SET POWER	STAND BY	kVA	250	275	300	330
			kW	200	220	240	264
		PRIME	kVA	227	250	273	300
			kW	182	200	218.4	240
	CANOPY DIMENSION (W x L x H) mm			1100x3100x2300	1100x3100x2300	1100x3100x2300	1100x3100x2300
	CANOPY WEIGHT kg			2400	2400	2600	2600
	OPEN DIMENSION (W x L x H) mm			1100x3100x2200	1100x3100x2200	1100x3100x2200	1100x3100x2200
	OPEN WEIGHT			2100	2100	2300	2300
ENGINE	BRAND			WILKINS	WILKINS	WILKINS	WILKINS
	TYPE			WL 206	WL 206	WL 263	WL 263
	POWER	STAND BY	kW	206	206	263	263
		PRIME	kW	187	187	210	210
	SPEED (rpm)			1500	1500	1500	1500
	CYCLE			4	4	4	4
	DISPLACEMENT (lt)			8,27	8,27	8,27	8,27
	NUMBER OF CYLINDERS			6 IN LINE	6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			114 X 135	114 X 135	114 X 135	114 X 135
	COMPRESSION RATIO			18 : 1	18 : 1	18:1	18:1
	GOVERNOR TYPE			ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED
	COMBUSTION SYSTEM			DIRECT	DIRECT	DIRECT	DIRECT
	COOLING SYSTEM			WATER	WATER	WATER	WATER
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		52	52	60,2	60,2
%75 PRIME POWER		39	39	44,68	44,68		
%50 PRIME POWER		27	27	30,6	30,6		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			30	30	40	40	
TOTAL COOLANT CAPACITY (lt)			48	48	52	52	
FUEL TANK CAPACITY (lt)			360	360	360	360	

Armak reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

Armak Makine Mühendislik İnş. San. ve Tic. Ltd. Şti.

Denizköşkler Mah. Tunay Sk. No:28
Avcılar / İSTANBUL / TURKEY

T: 0212 694 66 66

F: 0212 593 09 60

armakmakine@armakmakine.com

www.armakmakine.com